

방폭형 벤 에어 모터 V8 시리즈

EX-Vane Air Motor V8 Series



Model	V8-F	V8-L	V8-B	V8-N	V8-I
Mounting	Face	Foot	Butterfly	NEMA 145TC	IEC #72 D90 (Metric)
Performance at Maximum Speed					
Power	HP / kW		5.25 / 3.90		
Torque	N-m / lb-in		15 / 132		
Speed	rpm		3,000		
Air Consumption	l/min / CFM		4,955 / 175		
Mass	kg / lb	10.4 / 22.9	11 / 24.2	10.5 / 23.1	12 / 26.4
Performance at Maximum Torque					
Torque	N-m / lb-in		21 / 185		
Speed	rpm		300		
Recommended					
Air Service Unit	FRL 1/2				
Repair Kit	SK-V8 / SK-V8-8				

방폭형 벤 에어 모터 V16 시리즈

EX-Vane Air Motor V16 Series



Model	V16-F	V16-L	V16-LN	V16-N	V16-I
Mounting	Face	Foot	Foot / 145TC	NEMA 145TC	IEC #72 D100 (Metric)
Performance at Maximum Speed					
Power	HP / kW		9.5 / 7.08		
Torque	N-m / lb-in		34 / 300		
Speed	rpm		2,000		
Air Consumption	l/min / CFM		7,787 / 275		
Mass	kg / lb	32.94 / 73	32.9 / 73	80 / 36	32.9 / 73
Performance at Maximum Torque					
Torque	N-m / lb-in		43 / 380		
Speed	rpm		300		
Recommended					
Air Service Unit	FRL 1				
Repair Kit	SK-V16 / SK-V16-8				