

arium® mini Series



Type of System Feed Water

arium® mini	Pretreated water from a supply container
arium® mini Essential	Directly connects to a pretreated water supply line (RO/DI/EDI)
arium® mini Plus	Directly connects to tap water

arium® mini & mini essential

3차수 생산 장비



- Buffer, media and pH solutions
- Histology
- ELISA
- Solutions for chemical analysis and synthesis
- IC(Ion chromatography)
- ICP-MS
- GC-MS
- HPLC

- 일정한 수질의 3차수 생산
- Bagtank 시스템으로 Cleaning 필요없음
- 빠른 채수 속도
- 터치 스크린으로 손쉬운 사용
- 작고 실용적인 디자인
- 직수형 3차수 생산 장치로 Bagtank 없이 바로 1차수 공급 라인에 연결 (Essential)

Technical Specifications

Water type	Type 1
Water dispensing flow rate	Up to 1 l/min
Typical conductivity	0.055 $\mu\text{S}/\text{cm}$ compensated to 25 °C
Typical resistivity	18.2 M \times cm compensated to 25 °C
Microorganism content	< 1 CFU/1000 ml
Particle content	< 1/ml
TOC content (with UV lamp)	< 5 ppb

Ordering Information

Order No.	Description
H2O-MM-T	arium® mini bench top device, for manual feeding with pretreated feed water
H2O-MM-UV-T	arium® mini bench top device with UV lamp, for manual feeding with Pretreated feed water
H2O-MU-T	arium® mini essential, benchtop system; for direct connection to pretreated water supply
H2O-MU-UV-T	arium® mini mini essential, benchtop system with UV lamp
H2O-S-PACK	arium® Scientific Kit (1 pc)
H2O-CEL1	arium® UV lamp (185 254 nm), (1 pc)
H2O-CBS-5-S*	arium® 5 liter Bag (1 pc)
5441307H4-CE	arium® Sterile filter (Sartopore® 2 150 capsule) 0.2 μm pore size, (1 pc)
H2O-CUF	Ultrafilter for arium mini series and comfort series.

arium® mini plus

1차수 & 3차수 통합 생산 장비



- 1차수 & 3차수 생산 가능
- Bagtank 시스템으로 Cleaning 필요없음
- 빠른 채수 속도
- 터치스크린으로 손쉬운 사용
- 작고 실용적인 디자인

- 1차수 & 3차수 생산 가능
- Bagtank 시스템으로 Cleaning 필요없음
- 빠른 채수 속도
- 터치스크린으로 손쉬운 사용
- 작고 실용적인 디자인

Water type	Type 1	Type 3
Output	-	Up to 8 l/h
Water dispensing flow rate	Up to 1.0 l/min	Depressurized via ball valve
Typical conductivity	0.055 $\mu\text{S}/\text{cm}$ compensated to 25 °C	< 20 $\mu\text{S}/\text{cm}$
Typical resistivity	18.2 M \times cm compensated to 25 °C	< 0.05 M \times cm
Microorganism content	< 1CFU/1,000 ml	< 1CFU/1,000 ml
Particle content	< 1/ml	< 1/ml
TOC content (with UV lamp)	< 5 ppb	-
Typical ion retention	-	Up to 98 %
Retention of dissolved organic substances (MW>300 Dalton)	-	> 99 %

Ordering Information

Order No.	Description
H2O-MA-T	arium® mini plus, bench top device, flow capacity Type 3 pure water 8 l/h
H2O-MA-UV-T	arium® mini plus, bench top device with UV lamp, flow capacity Type 3 pure water 8 l/h
H2O-CPR	arium® mini plus Pre-treatment Cartridge (1 pc)
H2O-S-PACK	arium® Scientific Kit (1 pc)
H2O-CEL1	arium® UV lamp (185 254 nm), (1 pc)
H2O-CBS-5-S	arium® 5 liter Bag (1 pc)
5441307H4-CE	arium® Sterile filter (Sartopore® 2 150 capsule) 0.2 μm pore size, (1 pc)
H2O-CUF	Ultrafilter for arium mini series and comfort series.